



2019 Front Suspension Specifications

Oil Volume, Air Pressure, Coil Spring Rates, Bottomless Tokens™, and Technical Specifications



Oil Volume and Lubricant

| FORK | MODEL | WHEEL (in) | TRAVEL (mm) | DAMPER | | | | | | SPRING | | | | |
|-------------|-------------------------|--|-------------|--------------------|--------------------------|------------------------------|----------------------|-------------------------|-------------|-----------------------|---------------------------|--------------------|-------------------------|-------------|
| | | | | Damper | Upper Tube | | | Lower Leg | | Spring | Upper Tube | | Lower Leg | |
| | | | | | RockShox® Suspension Oil | Oil Height ¹ (mm) | Volume (mL) | RockShox Suspension Oil | Volume (mL) | | RockShox Oil or Lubricant | Volume (mL) | RockShox Suspension Oil | Volume (mL) |
| 30™ Gold | RL RL R [†] | 26 | 80-100 | Motion Control™ | 5wt | 80-85 | 85 | 15wt | 6 | Solo Air™ | 5wt | 5 | 15wt | 6 |
| | | 27.5 | 80-120 | | | | 102 | | | | | | | |
| | | 29 | | | | | | | | | | | | |
| 30 Silver | TK TK R [†] | 26 | 80-120 | Turnkey™ | 5wt | 80-85 | 100 | 15wt | 6 | Solo Air | 5wt | 5 | 15wt | 6 |
| | | 27.5 | | | | | Coil | | | PM600 or SRAM® Butter | Grease Coil Spring | 10 | | |
| | | | Solo Air | | | | 5wt | | | 5 | 6 | | | |
| | | | Coil | | | | PM600 or SRAM Butter | | | Grease Coil Spring | 10 | | | |
| | | 29 | 80-100 | | | | Solo Air | | | 5wt | 5 | 6 | | |
| Bluto™ | RL RL R [†] | 26 | 80-120 | Motion Control | 5wt | 71-77 | 106 | 15wt | 5 | Solo Air | SRAM Butter | Grease Air Pistons | 15wt | 5 |
| BoXXer® | World Cup (RC2) | 27.5 B [*] | 200 | Charger 2 Damper™ | 3wt | - | Bleed | 0w-30 | 10 | DebonAir™ | SRAM Butter | Grease Air Pistons | 0w-30 | 10 |
| | | 29 B [*] | 180-200 | | | | | | | | | | | |
| | RC | 27.5 B [*] | 200 | Charger Damper™ RC | | | 66 | | | | | | | |
| | | 29 B [*] | 180-200 | | | | | | | | | | | |
| Judy™ Gold | RL RL R [†] | 27.5 B [*] 29 B [*] | 80-120 | Motion Control | 5wt | 80-85 | 102 | 15wt | 5 | Solo Air | 5wt | 5 | 15wt | 6 |
| Judy Silver | TK TK R [†] | | | Turnkey | | | 122 | | | | | | | |

^{*}Boost
[†]Remote Adjust
¹Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Oil Volume and Lubricant

| FORK | MODEL | WHEEL (in) | TRAVEL (mm) | DAMPER | | | | | | SPRING | | | | |
|----------------|--|--------------------------------|-------------|-------------------|--------------------------|------------------------------|-------------|-------------------------|----------------------|--------------------|---------------------------|--------------------|-------------------------|-------------|
| | | | | Damper | Upper Tube | | | Lower Leg | | Spring | Upper Tube | | Lower Leg | |
| | | | | | RockShox® Suspension Oil | Oil Height ¹ (mm) | Volume (mL) | RockShox Suspension Oil | Volume (mL) | | RockShox Oil or Lubricant | Volume (mL) | RockShox Suspension Oil | Volume (mL) |
| Lyrik™ | RC2 RCT3 RCT R [†] RC RC R [†] | 27.5 B* 29 B* | 150-180 | Charger 2 Damper™ | 3wt | - | Bleed | 0w-30 | 10 | DebonAir™ | SRAM® Butter | Grease Air Pistons | 0w-30 | 10 |
| Paragon™ Gold | RL RL R [†] | 700c | 50-65 | Motion Control™ | 5wt | 80-85 | 87 | 15wt | 12 | Solo Air™ | 5wt | 5 | 15wt | 12 |
| Paragon Silver | TK TK R [†] | | | Turnkey™ | 100 | | Coil | | PM600 or SRAM Butter | Grease Coil Spring | | | | |
| PIKE® | RCT3 RCT R [†] RC RC R [†] | 27.5 B* | 120-160 | Charger 2 Damper | 3wt | - | Bleed | 0w-30 | 10 | DebonAir | SRAM Butter | Grease Air Pistons | 0w-30 | 10 |
| | | 29 B* | 120-150 | | | | | | | | | | | |
| | RC | 29+ | 110-160 | | | | | | | Charger Damper™ | | | | |
| REBA® | RL RL R [†] | 27.5 27.5 B* 29 29 B* | 100 | Motion Control | 5wt | 71-77 | 100 | 15wt | 5 | Solo Air | SRAM Butter | Grease Air Pistons | 15wt | 5 |
| | | | 120 | | | | 108 | | | | | | | |
| | | | 130-150 | | | | 136 | | | | | | | |
| Recon™ Gold | RL RL R [†] | 27.5 | 80-120 | Motion Control | 5wt | 80-85 | 133 | 15wt | 6 | Solo Air | 5wt | 5 | 15wt | 6 |
| | | | 130 | | | | 130 | | | | | | | |
| | | | 29 | | | | 80-130 | | | | | | | |

*Boost™
[†]Remote Adjust
¹Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Oil Volume and Lubricant

| FORK | MODEL | WHEEL (in) | TRAVEL (mm) | DAMPER | | | | | | SPRING | | | | | | | |
|-------------|---|--|-------------------|--------------------|--------------------------|------------------------------|-------------|-------------------------|-------------|---------------------------|-----------------------|--------------------|-------------------------|-------------|-----------|--|--|
| | | | | Damper | Upper Tube | | | Lower Leg | | | Spring | Upper Tube | | | Lower Leg | | |
| | | | | | RockShox® Suspension Oil | Oil Height ¹ (mm) | Volume (mL) | RockShox Suspension Oil | Volume (mL) | RockShox Oil or Lubricant | | Volume (mL) | RockShox Suspension Oil | Volume (mL) | | | |
| Recon™ | RL RL R [†] | 27.5 29 | 80-120 | Motion Control™ | 5wt | 80-85 | 118 | 15wt | 6 | Solo Air™ | 5wt | 5 | 15wt | 6 | | | |
| | | | 130-140 | | | | 150 | | | | | | | | | | |
| | | 27.5 B [*] | 80-150 | | | | 140 | | | | | | | | | | |
| | 29 B [*] | 80-140 | | | | | | | | | | | | | | | |
| | TK TK R [†] | 27.5 29 | 80-100 | Turnkey™ | | | 118 | | | Coil | PM600 or SRAM® Butter | Grease Coil Spring | | 10 | | | |
| Revelation™ | RC RC R [†] | 27.5 B [*] | 120-160 | Charger Damper™ RC | 3wt | - | 46 | 0w-30 | 10 | DebonAir™ | SRAM Butter | Grease Air Pistons | 0w-30 | 10 | | | |
| | | | 29 B [*] | | | | | | | | | | | | 120-150 | | |
| | | 27.5 B [*] | 120-160 | Motion Control | 5wt | 100-106 | 155 | | | | | | | | | | |
| | | 29 B [*] | 120-150 | | | | | | | | | | | | | | |
| RS-1™ | RLC RL R [†] | 27.5 | 100-130 | Charger 2 Damper™ | 3wt | - | Bleed | 15wt | 5 | Solo Air | SRAM Butter | Grease Air Pistons | 15wt | 5 | | | |
| | | 29 | 100-120 | | | | | | | | | | | | | | |
| Sektor™ | RL RL R [†] | 27.5 B [*] 29 B [*] | 80-150 | Motion Control | 5wt | 80-85 | 130 | 15wt | 6 | DebonAir | 5wt | 6 | 15wt | 6 | | | |
| SID® | World Cup World Cup R [†] RLC RLC R [†] RL RL R [†] | 27.5 B [*] 29 B [*] | 100 | Charger 2 Damper | 3wt | - | Bleed | 15wt | 5 | DebonAir | SRAM Butter | Grease Air Pistons | 15wt | 5 | | | |
| | | | 29 B [*] | | | | | | | | | | | | 110-120 | | |

^{*}Boost™
[†]Remote Adjust
¹Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Oil Volume and Lubricant

| FORK | MODEL | WHEEL (in) | TRAVEL (mm) | DAMPER | | | | | | SPRING | | | | |
|--------|----------------------|--|-------------|--------------------|--------------------------|------------------------------|-------------|-------------------------|-------------|-----------|---------------------------|--------------------|-------------------------|-------------|
| | | | | Damper | Upper Tube | | | Lower Leg | | Spring | Upper Tube | | Lower Leg | |
| | | | | | RockShox® Suspension Oil | Oil Height ¹ (mm) | Volume (mL) | RockShox Suspension Oil | Volume (mL) | | RockShox Oil or Lubricant | Volume (mL) | RockShox Suspension Oil | Volume (mL) |
| XC™ 30 | TK TK R ² | 27.5 | 80-120 | Turnkey™ | 5wt | 80-85 | 143 | - | - | Coil | PM600 or SRAM® Butter | Grease Coil Spring | - | - |
| | | 29 | 80-100 | | | | | | | | | | | |
| Yari™ | RC | 27.5 B ³ 29 B ³ | 150-180 | Charger Damper™ RC | 3wt | - | 57 | 0w-30 | 10 | DebonAir™ | SRAM Butter | Grease Air Pistons | 0w-30 | 10 |
| | | | | Motion Control™ | 5wt | 100-106 | 180 | | | | | | | |
| | | 29+ | 100-160 | | | | | | | | | | | |

³Boost™

²Remote Adjust

¹Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Air Spring Pressure

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|-----------|------------|------------------|------------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| 30™ Gold | Solo Air™ | 26 27.5 29 | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi |
| | | | 100 | | | | | | |
| | | 27.5 29 | 120 | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |
| 30 Silver | Solo Air | 26 27.5 29 | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi |
| | | | 100 | | | | | | |
| | | 27.5 | 120 | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |
| Bluto™ | Solo Air | 26 | 80 100 120 | 70-90 psi | 90-105 psi | 105-120 psi | 120-135 psi | 135+ psi | 200 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) | >220 lbs (>99 kg) | MAX PSI |
|---------|------------|------------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | | |
| BoXXer® | DebonAir™ | 27.5 B* 29 B* | 180 | <105 psi | 105-115 psi | 115-125 psi | 125-135 psi | 135-145 psi | 145-155 psi | 155+ psi | 200 psi |
| | | | 190-200 | <95 psi | 95-105 psi | 105-115 psi | 115-125 psi | 125-135 psi | 135-145 psi | 145+ psi | |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|-------------|------------|------------------|-------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| Judy™ Gold | Solo Air | 27.5 B* 29 B* | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi |
| | | | 100 120 | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |
| Judy Silver | Solo Air | 27.5 B* 29 B* | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi |
| | | | 100 120 | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |

Air Spring Pressure

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) | >220 lbs (>99 kg) | MAX PSI |
|--------|------------|------------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | | |
| Lyrik™ | DebonAir™ | 27.5 B* 29 B* | 150 160 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | 163 psi |
| | | | 170 180 | <45 psi | 45-55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95+ psi | 148 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <132 lbs (<60 kg) | 132-155 lbs (60-70 kg) | 155-176 lbs (70-80 kg) | 176-198 lbs (80-90 kg) | >198 lbs (>90 kg) | MAX PSI |
|---------------|------------|------------|-------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| Paragon™ Gold | Solo Air™ | 700c | 50 65 | 80-90 psi | 90-100 psi | 100-125 psi | 125-135 psi | 135+ psi | 165 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) | >220 lbs (>99 kg) | MAX PSI |
|-------|------------|------------------|-------------------|--------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | | |
| PIKE® | DebonAir | 27.5 B* 29 B* | 120 | <75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115-125 psi | 125+ psi | 194 psi |
| | | | 130 140 | <65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115+ psi | 163 psi |
| | | | 150 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | |
| | | 27.5 B* | 160 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | 194 psi |
| | | 29+ | 100 | <75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115-125 psi | 125+ psi | 194 psi |
| | | | 110 120 | <65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115+ psi | 163 psi |
| | | | 130 140 150 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | |
| | | | 160 | <45 psi | 45-55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95+ psi | 148 psi |

Air Spring Pressure

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) | >220 lbs (>99 kg) | MAX PSI |
|-----------|------------|------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | |
| PIKE® DJ™ | Solo Air™ | 26 | 100 | 100-115 psi | 115-130 psi | 130-145 psi | 145-160 psi | 160-175 psi | 175+ psi | 250 psi |
| | | | 140 | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115+ psi | 163 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|-------|------------|--------------------------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | |
| REBA® | Solo Air | 27.5 27.5 B* 29 29 B* | 100 | <70 psi | 70-90 psi | 90-105 psi | 105-120 psi | 120-135 psi | 135+ psi | 195 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|------|------------|--------------------------------|-------------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| REBA | Solo Air | 27.5 27.5 B* 29 29 B* | 120 | 70-90 psi | 90-105 psi | 105-120 psi | 120-135 psi | 135+ psi | 200 psi |
| | | | 130 140 150 | 65-85 psi | 75-100 psi | 85-115 psi | 95-125 psi | 125+ psi | 190 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|-------------|------------|------------|-------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| Recon™ Gold | Solo Air | 27.5 29 | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi |
| | | | 100 120 | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |
| | | | 130 | 40-60 psi | 60-75 psi | 75-90 psi | 90-105 psi | 105+ psi | 225 psi |

Air Spring Pressure

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI | | | | | |
|-----------|------------|--------------------------------|-------------|--------------------|------------------------|------------------------|------------------------|-------------------|-----------|-----------|------------|-------------|----------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | | | | | |
| Recon™ RL | Solo Air™ | 27.5 29 | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi | | | | | |
| | | 27.5 B* 29 B* | | | | | | | | | | | | |
| | | 27.5 29 | 100 120 | | | | | | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |
| | | 27.5 B* 29 B* | | | | | | | | | | | | |
| | | 27.5 27.5 B* 29 29 B* | 130 140 | | | | | | | | | | | 200 psi |
| | | 27.5 B* | | | | | | | | | | | | |
| 27.5 B* | 150 | | | | | | | | | | | | | |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) | >220 lbs (>99 kg) | MAX PSI |
|-------------|------------|------------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | | |
| Revelation™ | DebonAir™ | 27.5 B* 29 B* | 120 | <75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115-125 psi | 125+ psi | 194 psi |
| | | | 130 140 | <65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115+ psi | 163 psi |
| | | | | 150 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | |
| | | 27.5 B* | 160 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|-------|------------|------------|-------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| RS-1™ | Solo Air | 27.5 29 | 100 120 | 70-90 psi | 90-105 psi | 105-120 psi | 120-135 psi | 135+ psi | 200 psi |
| | | 27.5 | | | | | | | |

Air Spring Pressure

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|---------|------------|------------------|-------------------|--------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | |
| Sektor™ | DebonAir™ | 27.5 B* 29 B* | 80 | 90-110 psi | 110-125 psi | 125-140 psi | 140-160 psi | 160+ psi | 265 psi |
| | | | 100 120 | 50-70 psi | 70-85 psi | 85-100 psi | 100-120 psi | 120+ psi | 205 psi |
| | | | 130 140 150 | 40-60 psi | 60-75 psi | 75-90 psi | 90-105 psi | 105+ psi | 225 psi |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | >200 lbs (>90 kg) | MAX PSI |
|------|------------|------------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | |
| SID® | Solo Air | 27.5 B* 29 B* | 100 | <70 psi | 70-90 psi | 90-105 psi | 105-120 psi | 120-135 psi | 135+ psi | 195 psi |
| | | 29 B* | 110 120 | | | | | | | |

| FORK | AIR SPRING | WHEEL (in) | TRAVEL (mm) | <120 lbs (<55 kg) | 120-140 lbs (55-63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) | >220 lbs (>99 kg) | MAX PSI |
|-------|------------|------------------|-------------|--------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------------|---------|
| | | | | E-Bikes Add 10 psi | | | | | | | |
| Yari™ | DebonAir | 27.5 B* 29 B* | 150 160 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | 163 psi |
| | | | 170 180 | <45 psi | 45-55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95+ psi | 148 psi |
| | | 29+ | 100 | <75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115-125 psi | 125+ psi | 194 psi |
| | | | 110 120 | <65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105-115 psi | 115+ psi | 163 psi |
| | | | 130 140 | <55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95-105 psi | 105+ psi | |
| | | | 150 160 | <45 psi | 45-55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85-95 psi | 95+ psi | 148 psi |
| | | | 170 180 | <35 psi | 35-45 psi | 45-55 psi | 55-65 psi | 65-75 psi | 75-85 psi | 85+ psi | |

Coil Spring Rates

| FORK | <140 lbs (<63 kg) | 140-160 lbs (63-72 kg) | 160-180 lbs (72-81 kg) | 180-200 lbs (81-90 kg) | 200-220 lbs (90-99 kg) |
|-------------------|----------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| 30™ Silver | Silver X-Soft | Yellow Soft | Red Medium | Blue Firm | Black X-Firm |
| Recon™ TK | | | | | |
| XC™ 30 | | | | | |

Bottomless Tokens™

| FORK | SPRING | WHEEL (in) | TRAVEL (mm) | FACTORY INSTALLED TOKENS | MAXIMUM TOKENS |
|-----------|-----------|------------|-------------|--------------------------|----------------|
| Bluto™ | Solo Air™ | 26 | 80 | 4 | 4 |
| | | | 100 | 2 | 4 |
| | | | 120 | 0 | 4 |
| BoXXer® | DebonAir™ | 27.5 B* | 200 | 0 | 6 |
| | | | 29 B* | 180 | 2 |
| | | 190 | | 1 | 6 |
| | | 200 | | 0 | 6 |
| Lyrik™ | DebonAir | 27.5 B* | 150 | 2 | 5 |
| | | | 160 | 2 | 5 |
| | | | 170 | 1 | 4 |
| | | | 180 | 0 | 4 |
| | | 29 B* | 150 | 2 | 5 |
| | | | 160 | 2 | 5 |
| | | | 170 | 1 | 4 |
| | | | 180 | 0 | 4 |
| PIKE® DJ™ | Solo Air | 26 | 100 | 0 | 2 |
| | | | 140 | 2 | 4 |

| FORK | SPRING | WHEEL (in) | TRAVEL (mm) | FACTORY INSTALLED TOKENS | MAXIMUM TOKENS |
|------|----------|------------|-------------|--------------------------|----------------|
| PIKE | DebonAir | 27.5 B* | 120 | 3 | 6 |
| | | | 130 | 2 | 6 |
| | | | 140 | 1 | 5 |
| | | | 150 | 1 | 4 |
| | | | 160 | 0 | 4 |
| | | 29 B* | 120 | 3 | 6 |
| | | | 130 | 2 | 6 |
| | | | 140 | 1 | 5 |
| | | 29+ | 150 | 1 | 4 |
| | | | 120 | 4 | 7 |
| | | | 130 | 3 | 6 |
| | | | 140 | 3 | 6 |
| | | | 150 | 2 | 5 |
| | | | 160 | 2 | 5 |

Bottomless Tokens™

| FORK | SPRING | WHEEL (in) | TRAVEL (mm) | FACTORY INSTALLED TOKENS | MAXIMUM TOKENS |
|-------------|-----------|------------------|-------------|--------------------------|----------------|
| REBA® | Solo Air™ | 27.5 27 B* | 100 | 0 | 3 |
| | | | 120 | 0 | 3 |
| | | | 130 | 2 | 3 |
| | | | 140 | 1 | 3 |
| | | | 150 | 0 | 3 |
| | | 29 29 B* | 100 | 0 | 3 |
| | | | 120 | 0 | 3 |
| | | | 130 | 2 | 3 |
| | | | 140 | 1 | 3 |
| | | | 150 | 0 | 3 |
| Revelation™ | DebonAir™ | 27.5 B* 29 B* | 120 | 4 | 6 |
| | | | 130 | 3 | 6 |
| | | | 140 | 2 | 5 |
| | | | 150 | 1 | 4 |
| | | 27.5 B* | 160 | 0 | 4 |
| RS-1™ | Solo Air | 27.5 29 | 100 | 2 | 3 |
| | | | 120 | 0 | 3 |
| | | 27.5 | 130 | 0 | 3 |

| FORK | SPRING | WHEEL (in) | TRAVEL (mm) | FACTORY INSTALLED TOKENS | MAXIMUM TOKENS |
|---------|----------|------------------|-------------|--------------------------|----------------|
| Sektor™ | DebonAir | 27.5 B* 29 B* | 80 | 0 | 2 |
| | | | 100 | 0 | 2 |
| | | | 120 | 0 | 2 |
| | | | 130 | 0 | 2 |
| | | | 140 | 0 | 2 |
| | | | 150 | 0 | 2 |
| SID® | DebonAir | 27.5 B* 29 B* | 100 | 0 | 3 |
| | | | 29 B* | 110 | 1 |
| | | 29 B* | 120 | 0 | 3 |
| Yari™ | DebonAir | 27.5 B* 29 B* | 150 | 2 | 5 |
| | | | 160 | 2 | 5 |
| | | | 170 | 1 | 4 |
| | | | 180 | 0 | 4 |
| | | 29+ | 100 | 5 | 7 |
| | | | 110 | 5 | 7 |
| | | | 120 | 4 | 7 |
| | | | 130 | 3 | 6 |
| | | | 140 | 3 | 6 |
| 150 | 2 | 5 | | | |
| 160 | 2 | 5 | | | |

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) | | | | | | | | |
|----------|-----------------|------------|-------------|---------------|---|------------------------|----------------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|------------------------|------|-----|-----|-----|-----|-----|----|
| 30™ Gold | 30 | 26 | 80 | Solo Air™ | Motion Control™ | 1 1/8 Aluminum | 9 QR | 40 | 453 | 160 | 220 | 680 | 58 | | | | | | | | |
| | | | 100 | | | | | | 473 | | | | | | | | | | | | |
| | | 27.5 | 80 | | | 1 1/8 Aluminum Tapered | | 468 | 710 | | | | | | | | | | | | |
| | | | 100 | | | | | 488 | | | | | | | | | | | | | |
| | | | 120 | | | | | 508 | | | | | | | | | | | | | |
| | | 29 | 80 | | | Tapered | | 487 | 62 | | | | | | | | | | | | |
| | | | 100 | | | | | 507 | | | | | | | | | | | | | |
| | | | 120 | | | | | 527 | | | | | | | | | | | | | |
| | | 30 Silver | 30 | | | 26 | | 80 | Solo Air | | | Turnkey™ | | 1 1/8 Aluminum Tapered | 9 QR | 40 | 455 | 160 | 220 | 680 | 58 |
| | | | | | | | | 100 | 475 | | | | | | | | | | | | |
| 27.5 | 80 | | | Coil Solo Air | 1 1/8 Aluminum 1 1/8 Steel Tapered | 470 | 710 | | | | | | | | | | | | | | |
| | 100 | | | | | 490 | | | | | | | | | | | | | | | |
| | 120 | | | | | 510 | | | | | | | | | | | | | | | |
| 29 | 80 | | | Tapered | 489 | 62 | | | | | | | | | | | | | | | |
| | 100 | | | | 509 | | | | | | | | | | | | | | | | |
| | 120 | | | | 527 | | | | | | | | | | | | | | | | |
| Bluto™ | 32 | | | 26 | 80 | Solo Air | Motion Control | Tapered | 15 x 150 | 51 | 491 | | 160 | 220 | | 760 | 116 | | | | |
| | | | | | 100 | | | | | | 511 | | | | | | | | | | |
| | | 120 | 531 | | | | | | | | | | | | | | | | | | |
| BoXXer® | 35 | 27.5 B* | 200 | DebonAir™ | Charger 2 Damper™ Charger Damper™ RC | 1 1/8 Aluminum | 20 x 110 | 48 | 581 | 200 | 220 | 732 | 81 | | | | | | | | |
| | | | 180 | | | | | | 582 | | | | | | | | | | | | |
| | | 29 B* | 190 | | | | | 592 | 770 | | | | | | | | | | | | |
| | | | 200 | | | | | 602 | | | | | | | | | | | | | |

*Boost™

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) |
|------------------|-----------------|------------|-------------|-----------|-------------------|--|-----------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|
| Judy™ Gold | 30 | 27.5 B* | 80 | Solo Air™ | Motion Control™ | Tapered | 15 x 110 | 42 51 | 472 | 160 | 220 | 732 | 81 |
| | | | 100 | | | | | | 492 | | | | |
| | | | 120 | | | | | | 512 | | | | |
| | | 29 B* | 80 | | | | | 490 | | | | | |
| | | | 100 | | | | | 510 | | | | | |
| | | | 120 | | | | | 530 | | | | | |
| Judy Silver | 30 | 27.5 B* | 80 | Solo Air | Turnkey™ | Tapered | 15 x 110 | 42 51 | 470 | 160 | 220 | 732 | 81 |
| | | | 100 | | | | | | 490 | | | | |
| | | | 120 | | | | | | 510 | | | | |
| | | 29 B* | 80 | | | | | 490 | | | | | |
| | | | 100 | | | | | 510 | | | | | |
| | | | 120 | | | | | 530 | | | | | |
| Lyrik™ | 35 | 27.5 B* | 150 | DebonAir™ | Charger 2 Damper™ | Tapered | 15 x 110 | 37 46 | 542 | 180 | 220 | 732 | 81 |
| | | | 160 | | | | | | 552 | | | | |
| | | | 170 | | | | | | 562 | | | | |
| | | | 180 | | | | | | 572 | | | | |
| | | 29 B* | 150 | | | | | 562 | | | | | |
| | | | 160 | | | | | 572 | | | | | |
| | | | 170 | | | | | 582 | | | | | |
| | | | 180 | | | | | 592 | | | | | |
| Paragon™ Gold RL | 30 | 700c | 50 | Solo Air | Motion Control | 1 1/8 Aluminum 1 1/8 Aluminum XL Tapered | 9 QR | 46 | 462 | 160 | 180 | 716 | 45 |
| | | | 65 | | | | | | 477 | | | | |

*Boost™

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) |
|-------------------|-----------------|------------|-------------|-----------|-------------------|---------------------------------------|-----------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|
| Paragon Silver TK | 30 | 700c | 50 | Coil | Turnkey™ | 1 1/8 Steel 1 1/8 Steel XL Tapered | 9 QR | 46 | 462 | 160 | 180 | 716 | 45 |
| | | | 65 | | | | | | 477 | | | | |
| PIKE® DJ™ | 35 | 26 | 100 | Solo Air™ | Charger Damper™ | Tapered | 15 x 100 | 40 | 482 | 160 | 220 | 694 | 66 |
| | | | 140 | | | | | | 522 | | | | |
| PIKE | 35 | 27.5 B* | 120 | DebonAir™ | Charger 2 Damper™ | Tapered | 15 x 110 | 37 46 | 512 | 180 | 220 | 732 | 81 |
| | | | 130 | | | | | | 522 | | | | |
| | | | 140 | | | | | | 532 | | | | |
| | | | 150 | | | | | | 542 | | | | |
| | | | 160 | | | | | | 552 | | | | |
| | | 29 B* | 120 | | | | | 531 | 770 | | | | |
| | | | 130 | | | | | 541 | | | | | |
| | | | 140 | | | | | 551 | | | | | |
| | | | 150 | | | | | 561 | | | | | |
| | | 29+ | 100 | | | | | 523 | 786 | | | 82 | |
| | | | 110 | | | | | 533 | | | | | |
| | | | 120 | | | | | 543 | | | | | |
| | | | 130 | | | | | 553 | | | | | |
| | | | 140 | | | | | 563 | | | | | |
| | | | 150 | | | | | 573 | | | | | |
| | | | 160 | | | | | 583 | | | | | |

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) | |
|-------|-----------------|------------|-------------|-----------|-----------------|-------------------|-----------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|----|
| REBA® | 32 | 27.5 | 100 | Solo Air™ | Motion Control™ | Tapered | 15 x 100 | 42 | 487 | 160 | 220 | 714 | 62 | |
| | | | 120 | | | | | | 507 | | | 710 | | |
| | | | 130 | | | | | | 517 | | | 717 | | |
| | | | 140 | | | | | | 527 | | | | | |
| | | | 150 | | | | | | 537 | | | | | |
| | | 27.5 B* | 100 | | | | | | 487 | | | 714 | | |
| | | | 120 | | | | | | 507 | | | 712 | | |
| | | | 130 | | | | | | 517 | | | 714 | | 81 |
| | | | 140 | | | | | | 527 | | | | | |
| | | | 150 | | | | | | 537 | | | | | |
| | | 29 | 100 | | | | 506 | 755 | 62 | | | | | |
| | | | 120 | | | | 526 | | | | | | | |
| | | | 130 | | | | 536 | | | | | | | |
| | | | 140 | | | | 546 | | | | | | | |
| | | | 150 | | | | 556 | | | | | | | |
| | | 29 B* | 100 | | | | 506 | | | | | 760 | 81 | |
| | | | 120 | | | | 526 | | | | | | | |
| | | | 130 | | | | 536 | | | | | | | |
| | | | 140 | | | | 546 | | | | | | | |
| | | | 150 | | | | 556 | | | | | | | |

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) |
|-------------------|-----------------|------------|-------------|-----------|-----------------|------------------------|------------------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|
| Recon™ Gold RL | 32 | 27.5 | 80 | Solo Air™ | Motion Control™ | Tapered | 15 x 100 | 42 | 469 | 160 | 220 | 714 | 62 |
| | | | 100 | | | | | | 489 | | | | |
| | | | 120 | | | | | | 509 | | | | |
| | | | 130 | | | | | | 519 | | | | |
| | | 29 | 80 | | | | | 489 | 755 | | | | |
| | | | 100 | | | | | 509 | | | | | |
| | | | 120 | | | | | 529 | | | | | |
| | | | 130 | | | | | 538 | | | | | |
| Recon RL | 32 | 27.5 | 80 | Solo Air | Motion Control | 1 1/8 Aluminum Tapered | 9 QR 15 x 100 | 42 | 466 | 160 | 220 | 710 | 62 |
| | | | 100 | | | | | | 486 | | | | |
| | | | 120 | | | | | | 506 | | | | |
| | | | 130 | | | | | | 520 | | | | |
| | | | 140 | | | | | | 530 | | | | |
| | | 27.5 B* | 80 | | | 470 | 717 | | | | | | |
| | | | 100 | | | 490 | | | | | | | |
| | | | 120 | | | 510 | | | | | | | |
| | | | 130 | | | 520 | | | | | | | |
| | | | 140 | | | 530 | | | | | | | |
| | | 150 | 150 | | | 540 | 81 | | | | | | |
| | | | 150 | | | 540 | | | | | | | |
| | | | 150 | | | 540 | | | | | | | |
| | | | 150 | | | 540 | | | | | | | |
| 150 | 540 | | | | | | | | | | | | |

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) |
|-------------|-----------------|------------|-------------|-----------|-----------------------------------|------------------------|---------------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|
| Recon™ RL | 32 | 29 | 80 | Solo Air™ | Motion Control™ | 1 1/8 Aluminum Tapered | 9 QR 15 x 100 | 46 51 | 485 | 160 | 220 | 755 | 62 |
| | | | 100 | | | | | | 505 | | | | |
| | | | 120 | | | | | | 525 | | | | |
| | | | 130 | | | | | | 539 | | | | |
| | | | 140 | | | | | | 549 | | | | |
| | | 29 B* | 80 | | | Tapered | 15 x 100 | 51 | 489 | | | | |
| | | | 100 | | | | | | 509 | | | | |
| | | | 120 | | | | | | 529 | | | | |
| | | | 130 | | | | | | 539 | | | | |
| | | | 140 | | | | | | 549 | | | | |
| Recon TK | 32 | 27.5 | 80 | Coil | Turnkey™ | 1 1/8 Steel Tapered | 9 QR 15 x 100 | 42 | 466 | 160 | 220 | 710 | 62 |
| | | | 100 | | | | | | 486 | | | | |
| | | 29 | 80 | | | | | | 46 51 | | | 485 | |
| | | | 100 | | | | | | | | | 505 | |
| | | | 755 | | | | | | | | | | |
| | | | 505 | | | | | | | | | | |
| Revelation™ | 35 | 27.5 B* | 120 | DebonAir™ | Charger Damper RC™ Motion Control | Tapered | 15 x 110 | 37 46 | 512 | 180 | 220 | 732 | 82 |
| | | | 130 | | | | | | 522 | | | | |
| | | | 140 | | | | | | 532 | | | | |
| | | | 150 | | | | | | 542 | | | | |
| | | | 160 | | | | | | 552 | | | | |
| | | 29 B* | 120 | | | | | | 42 51 | | | 531 | |
| | | | 130 | | | | | | | | | 541 | |
| | | | 140 | | | | | | | | | 551 | |
| | | | 770 | | | | | | | | | | |
| | | | 150 | | | | | | | | | 561 | |

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) |
|---------|-----------------|------------------|-------------|-----------|-------------------|--|----------------------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|
| RS-1™ | 32 | 27.5 | 100 | Solo Air™ | Charger 2 Damper™ | Tapered Carbon | Predictive Steering™ | 42 | 497 | 160 | 220 | 710 | 62 |
| | | | 120 | | | | | | 507 | | | | |
| | | | 130 | | | | | | 517 | | | | |
| | | 29 | 100 | | | | | 516 | 751 | | | | |
| | | | 120 | | | | | 526 | | | | | |
| Sektor™ | 32 | 27.5 B* 29 B* | 80 | DebonAir™ | Motion Control™ | Tapered | 15 x 110 | 46 | 474 | 160 | 220 | 732 | 81 |
| | | | 100 | | | | | | 494 | | | | |
| | | | 120 | | | | | | 514 | | | | |
| | | | 130 | | | | | | 524 | | | | |
| | | | 140 | | | | | | 534 | | | | |
| | | | 150 | | | | | | 544 | | | | |
| SID® | 32 | 27.5 B* | 100 | DebonAir | Charger 2 Damper | Tapered Tapered Carbon | 15 x 110 | 42 | 487 | 160 | 220 | 714 | 81 |
| | | | 110 | | | 506 | | | 755 | | | | |
| | | 29 B* | 120 | | | 521 | | 760 | | | | | |
| | | | 120 | | | 531 | | | | | | | |
| | | | 120 | | | 531 | | | | | | | |
| XC™ 30 | 30 | 27.5 | 80 | Coil | Turnkey™ | 1 1/8 Aluminum 1 1/8 Steel Tapered | 9 QR | 42 | 470 | 160 | 220 | 710 | 62 |
| | | | 100 | | | | | | 490 | | | | |
| | | | 120 | | | | | | 510 | | | | |
| | | 29 | 80 | | | 489 | | 755 | | | | | |
| | | | 100 | | | 46 | | | 509 | | | | |
| | | | | | | 51 | | | | | | | |

Technical Specifications

| FORK | UPPER TUBE (mm) | WHEEL (in) | TRAVEL (mm) | SPRING | DAMPER | STEERER TUBE (in) | AXLE (mm) | OFFSET (mm) | AXLE TO CROWN (mm) | ROTOR DIAMETER MIN (mm) | ROTOR DIAMETER MAX (mm) | TIRE DIAMETER MAX (mm) | TIRE WIDTH MAX (mm) |
|-------|-----------------|------------|-------------|-----------|---------------------------------------|-------------------|-----------|-------------|--------------------|-------------------------|-------------------------|------------------------|---------------------|
| Yari™ | 35 | 27.5 B* | 150 | DebonAir™ | Charger Damper RC™ Motion Control™ | Tapered | 15 x 110 | 37 46 | 542 | 180 | 220 | 732 | 81 |
| | | | 160 | | | | | | 552 | | | | |
| | | | 170 | | | | | | 562 | | | | |
| | | | 180 | | | | | | 572 | | | | |
| | | 29 B* | 150 | | | | | 561 | 770 | | | | |
| | | | 160 | | | | | 571 | | | | | |
| | | | 170 | | | | | 581 | | | | | |
| | | | 180 | | | | | 591 | | | | | |
| | | 29+ | 100 | | | | | 523 | 786 | | | 82 | |
| | | | 110 | | | | | 533 | | | | | |
| | | | 120 | | | | | 543 | | | | | |
| | | | 130 | | | | | 553 | | | | | |
| | | | 140 | | 563 | | | | | | | | |
| | | | 150 | | 573 | | | | | | | | |
| | | | 160 | | 583 | | | | | | | | |

This publication includes a trademark from the following company:

Boost™ is a trademark owned by Trek Bicycle Corporation.

SRAM®

www.sram.com



ASIAN HEADQUARTERS
SRAM Taiwan
No. 1598-8 Chung Shan Road
Shen Kang Hsiang, Taichung City
Taiwan R.O.C.

WORLD HEADQUARTERS
SRAM LLC
1000 W. Fulton Market, 4th Floor
Chicago, Illinois 60607
U.S.A.

EUROPEAN HEADQUARTERS
SRAM Europe
Paasbosweg 14-16
3862ZS Nijkerk
The Netherlands